
GROUP 31

WHEEL AND TIRE

CONTENTS

GENERAL INFORMATION 31-2 **TIRE PRESSURE MONITORING SYSTEM (TPMS) 31-2**

GENERAL INFORMATION

M2310000101308

The 18-inch aluminum type road wheel and tire and the 18-inch steel type spare wheel and tire are adopted.

Lead-free component

- Lead has been eliminated from the balance weight.

Hexavalent chromium-free component

- Hexavalent chromium has been eliminated from the wheel, nut, and balance weight.

SPECIFICATIONS

ROAD WHEEL AND TIRE

Item		GSR	MR
Wheel	Type	Aluminum type	Aluminum type
	Size	18 × 8.5JJ*	18 × 8.5JJ (BBS)
	Amount of wheel offset mm (in)	38 (1.5)	38 (1.5)
	PCD mm (in)	114.3 (4.50)	114.3 (4.50)
Tire	Size	245/40R18 93Y	245/40R18 93Y

NOTE:

- *: The ENKEI casted aluminum wheel is equipped as standard, and the BBS forged aluminum wheel is equipped as an option.
- PCD indicates the pitch circle diameter of the wheel installation holes.

SPARE WHEEL AND TIRE

Item		Specification
Wheel	Type	Steel type
	Size	18 × 4T
	Amount of wheel offset mm (in)	30 (1.2)
	PCD mm (in)	114.3 (4.50)
Tire	Size	T145/70R18 107M

NOTE: PCD indicates the pitch circle diameter of the wheel installation holes.

TIRE PRESSURE MONITORING SYSTEM (TPMS)

M2310000200078

Refer to GROUP 42B – Keyless Operation System (KOS) [P.42B-21](#) or GROUP 42C – Wireless Control Module (WCM) [P.42C-10](#).