GROUP 31 WHEEL AND TIRE

CONTENTS

GENERAL INFORMATION

- The wheels and tires of the following specifications have been established.
- Adopt the Tire Pressure Monitoring System (TPMS).
 - · Warns driver of low tire pressure by illuminating the TPMS warning light on the combination meter.

SPECIFICATIONS

 Warns driver of TPMS probrems by flashing^{*} the TPMS warning light on the combination meter.

M2310000101751

NOTE: *: Change to continuous illumination after flashing for about 1 minute.

Item		2.0L Engine		2.4L Engine
		Vehicles for CANADA	Except for CANADA	-
TPMS warning pressure kPa (psi)	Warning ON	189 (27.4) or less	189 (27.4) or less	174 (25.2) or less
	Warning OFF	204 (29.6) or more	204 (29.6) or more	189 (27.4) or more
Wheel	Туре	Aluminum type	Aluminum type	Aluminum type
	Size	18 × 7JJ	18 × 7JJ	$18 \times 7 JJ$
	Amount of wheel offset mm (in)	46 (1.8)	46 (1.8)	46 (1.8)
	PCD mm (in)	114.3 (4.50)	114.3 (4.50)	114.3 (4.50)
Tire	Size	P215/45R18 89V	215/45R18 89W	P215/45R18 89V

NOTE: PCD indicates the pitch circle diameter of the wheel installation holes.

SPARE WHEEL AND TIRE

Item		2.0L Engine	2.4L Engine	
Wheel	Туре	Steel type	Steel type	
	Size	16 × 4T	16 × 4T	
	Amount of wheel offset mm (in)	40 (1.6)	40 (1.6)	
	PCD mm (in)	114.3 (4.50)	114.3 (4.50)	
Tire	Size	T125/90D16 98M	T125/70D16 96M	

NOTE: PCD indicates the pitch circle diameter of the wheel installation holes.

TIRE PRESSURE MONITORING SYSTEM (TPMS)

Refer to GROUP 42B – Keyless Operation System (KOS) P.42B-20 or GROUP 42C - Wireless Control Module (WCM) P.42C-9.